

# TOVCOL TP5

## VYNIL GLUE FOR T/G PARQUET AND FLOATING LAMINATED FLOORS

Acetovynil-adhesive in water dispersion to lay T/G wooden floors or floating laminated floors. After a very fast setting, it creates a completely transparent film belonging to D3 water-resistance class, according to the EN204 norm. Tovcol TP5 is also suitable for gluing small wooden parts exposed to water, also in do-it-yourself jobs.



### Technical data

| <b>Physical characteristics (20°C – 60% R.H.)</b> |  |   |                        |
|---|--|---|------------------------|
| Aspect  | White paste  | Specific weight                               | 1,10 g/cm <sup>3</sup> |
| Viscosity   | 9000-15000 mPa·s                                   | Dry residue                                   | 50 +/- 1 %             |
| <b>Times (20°C – 60% R.H.)</b>                    |  |   |                        |
| Open time   | 10'  | Complete hardening                            | 24-48 h                |
| Set to traffic                                    | 12-24 h  | Minimum Film Form. Temp.                      | ~4 °C                  |
| <b>Technical features</b>                         |  |   |                        |
| Yield   | ~100- 150 ml/sqm                                   | Durability class according to DIN EN 204 norm | D3                     |
| Linear yield                                      | ~10- 25 ml/linear mt                               | Application temperature                       | > + 10°C               |
| <b>Storage and labelling</b>                      |  |   |                        |
| Storage in original packaging closed at T>+ 10°C  | 12 months (protect from freeze)                    | Symbols of risk                               | NONE                   |
| <b>Tools cleaning</b>                             | With water immediately after use, when still fresh |   |                        |
| <b>Packaging</b>                                  | Bottle of 500 ml                                   |   |                        |

### Application

Tovcol TP5 is available in bottles with pouring lip. Cut the lip according to the required quantity of adhesive. Insert the lip inside the space between the two leaves and squeeze the bottle. Make pressure to promote the adhesion.

Important. The wooden surfaces to be joint must be carefully cleaned removing any trace of detaching substance (oils, waxes, dust...)

### Notes

- ✓ Stains of glue will have to be immediately removed with a damp pad.
- ✓ It is possible to remove the dry film only mechanically.

### Norms references

UNI EN 14342:2008 Wood flooring - Characteristics, evaluation of conformity and marking.  
UNI EN 205:2006 Adhesives - Wood adhesives for non-structural applications - Determination of tensile shear strength of lap joints. UNI EN 204:2001 Classification of thermoplastic wood adhesives for non-structural applications

### Safety rules

FOR PROFESSIONAL USE ONLY. Strictly respect the information reported on the labels and consult safety data sheets before use.

### Disposing of waste

Dispose not used product and empty containers in accordance of local in force regulations.

**WARNING:** The information reported in present technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated.

**REV.4 18-07-2013** Current Technical Data Sheet replaces the previous one.



**TOVER S.R.L.**  
Via Rosa Luxembourg 2/A  
10093 COLLENO (TO)  
P.IVA 07783540011  
R.E.A. n°920259  
Tel.: +39-011/7792823  
Fax: +39-011/7792749  
[www.tover.com](http://www.tover.com)  
e-mail: [info@tover.com](mailto:info@tover.com)  
Made in Italy

