

# Pro-Deck

## Water-based impregnation product for outdoor wooden floorings

Water-based impregnation agent for the protection treatment of wooden floorings and other surfaces outside (decking, terraces, pools, furniture, etc.).

Pro-Deck deeply penetrates into the wood and preserves the surfaces from spots, UV rays, moss and lichens. It reduces humidity absorption leaving the wood breathe. It is easy to apply and refresh, it does not become yellow, does not crack.

Pro-Deck exists in neutral (slightly amber) and coloured version.

### Technical data at 20 °C - 60% r.h

Aspect	Coloured liquid
Density	0,95 – 0,98 kg/litre
Gloss Level (60°)	5 – 7 gloss
Yield	10 – 12 m <sup>2</sup> /litre
Application temperature	> 10 °C
Touch dry	15 – 20 minutes
Overcoating	3 – 4 hours
Complete hardening	12 – 24 hours
Storage	12 months in original packaging at a temperature > 10 °C
VOC	25 g/litre, cat A/e (WB), limit 130 g/litre (2004/42/CE)
Thinner	Water
Tool cleaning	Clean the roller immediately after use with water and neutral soap till the water is transparent. Rinse with clean water. Store the rollers in diluted S/28 solution; rinse with water before use
Packaging	1 litre, 2,5 litres, 10 litres

### Use

**New or fresh sanded wood** – Thoroughly clean the dust and apply one or two coats of Pro-Deck with a brush or roller. In the case of greasy and oily woods normally one coat is sufficient, in the other cases two coats are necessary. There is no need to sand between one hand and another.

**Wood previously treated with oil** – Wash the floor with undiluted Re-Wood to remove all traces of old oil, then rinse thoroughly with water. If necessary, repeat the operation a second time. If grey areas are present, perform a Grey Free treatment followed by an abundant water wash. Once dry, apply one or two coats of Pro-Deck as in the case of new wood.

**Wood previously treated with Pro-Deck** – Wash the floor with diluted Deck-Soap (2 caps in 10 liters of water) and rinse with water. Any grey areas can be treated with Grey Free. After rinsing and drying, apply a coat of Pro-Deck.

### Maintenance

In order to clean a wooden floor treated with Pro-Deck, use Deck-Soap or Pulito Parquet detergents.



Varnishes & Finishing

## Pro-Deck



### Certifications



**TOVER**<sup>®</sup>



Tover S.r.l.  
Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY  
P. IVA 07783540011 - REA n. 920259  
Tel. +39/011.7792823 - Fax. +39/011.7792749  
www.tover.com - info@tover.com

## Notes

Stir before use to guarantee the colour

Before treating the whole surface, make some tests on a small area

The colours of the samples are indicative, please always make a test to determine the color in the real conditions of use.

Pay attention to the batch numbers of the coloured products. Always use a single batch for each coat. If that is not possible, mix the different batches together before applying.

The pigments absorb UV rays and slow down the natural wood deterioration

It is recommended to use the product at a temperature superior to +10°C

## Safety Rules

Product for professional use. Strictly respect what is expressed in the labeling and consult the safety data sheet before using the product.

## Disposing of waste

Dispose of the unused product and empty packages in accordance with the local legislation in force



Varnishes &  
Finishing

## Pro-Deck



## Certifications



The information reported in present technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated.  
Rev 03 – 07/04/2022. This technical data sheet replaces all the previous one.

**TOVER**<sup>®</sup>



Tover S.r.l.

Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY  
P. IVA 07783540011 - REA n. 920259  
Tel. +39/011.7792823 - Fax. +39/011.7792749  
[www.tover.com](http://www.tover.com) - [info@tover.com](mailto:info@tover.com)