

Riflex B12

Liquid wax

Liquid wax for the protection and maintenance of untreated, waxed and oiled wood. Based on beeswax and carnauba wax, nourishes, revives and protects wooden surfaces giving a natural velvet effect

Technical data at 20 °C – 60% r.h.

Appearance	Opalescent liquid
Density	0,810 kg/litre
Walkability	1 hour
Can be polished after	1 hour
Indicative yield	30 – 40 m ² /litre
Application temperature	From + 5 to + 35 °C
Tool cleaning	Greencleaner
Storage	24 24 months in original sealed packaging
Packaging	500 ml bottles with vaporizer, cans of 1 liter

Application procedure

Shake well before use. Apply the product on the wood to be treated with the sprayer or with a brush or cloth. After about 1 hour, polish with a soft cloth or, if applicable of floors, with single disc machine equipped with a white pad. After 1 – 2 hours it is possible to repeat the treatment for better protection.

It is possible to revive the appearance of wood treated with Riflex B12 even after some time carrying out a new polishing.

Note

Don't overdo the quantity.

Always polish the treated surfaces.

The product is not subject to freezing, but at low temperatures the waxes can solidify; should it happen, simply bring the product to a warm environment before application or immerse the tightly closed package in hot water.

Safety regulations

PRODUCT FOR PROFESSIONAL USE: Strictly comply with what is stated on the label and consult the safety data sheet before using the product.

Disposal

Dispose of the unused product and empty packaging in accordance with the local legislation in force.



Cleaning & maintenance

Riflex B12



Certifications



The recommendations of this technical data sheet are given for information only and do not bind our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend checking the actual suitability for the intended use.

Rev 02 – 12/05/2020. This technical data sheet replaces the previous one.