

Sigil Clack

Sealant for click joint or tongue and groove floors



Adhesives
and sealants

Sigil Clack

One-component fluid sealant, in water dispersion, for sealing click joints or tongue and groove joints both in wood and in laminate, in particular some types suitable for repositioning. Sigil Clack is indispensable in rooms subject to high humidity such as kitchens, bathrooms, entrances and public places, in order to avoid any swelling of the joints. The product is applied easily thanks to the practical spout, guarantees a good fast setting and is extremely easy to clean.

Technical data at 20 °C, 60% r.h.

Appearance	Milky liquid
Density	1,05 kg/litre
Open time	5 – 10 minutes
Walkability	12 – 24 hours
Setting time	1 – 2 hours
Complete hardening	24 – 48 hours
Yield	Approximately 30 – 40 m ² per 500 ml bottle
Application temperature	> + 10 °C
Storage	12 months in original sealed packaging at temp. > 10 °C – Protect from frost
Tools cleaning	With water, immediately after use
Packages available	500 ml bottles



Certifications



How to use

Make sure that the surfaces to be treated are clean and dry. Cut the dispenser nozzle on the Sigil Clack bottle with the section of the necessary dimensions. Apply the sealant on the tapping of an element of the flooring and immediately proceed with the joint; it is recommended to exert a slight pressure to favour a continuous sealing.

There are two ways to eliminate any excess product that is overflowed during the joining of the elements:

Cleaning after drying: when the sealant has dried, trim the seals by removing the product with your hands or, if necessary, using a suitable tool, taking care not to scratch the painted surface. Once hardened, Sigil Clack does not adhere to pre-painted surfaces, so it can be easily removed without using solvents.

Immediate cleaning: immediately after joining an element, remove the bordered sealant with the aid of a slightly damp sponge or cloth. This operation is recommended in the case of laying pre-finished elements with bevels.



Adhesives
and Sealants

Notes

Once hardened, Sigil Clack loses its white colour and becomes completely transparent. Although the elements are already blocked a few hours after installation, it is recommended to wait at least 12-24 hours before walking on the flooring; during this period the product develops its mechanical properties and any local stress could affect the continuity of the seal.

Always follow the installation instructions provided by the flooring manufacturer

Safety regulations

PRODUCT FOR PROFESSIONAL USE. Strictly comply with what is stated on the labelling and consult the safety data sheet before using the product.

Disposal

Dispose of the unused product and empty packaging in accordance with the provisions of the local legislation in force.

Sigil Clack



Certifications



The recommendations in this technical data sheet are given for information only and do not bind our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend checking the actual suitability for the intended use.

Rev 06 – 17/05/2022 This technical data sheet replaces the previous one.