



Solvent-based cleaner for the removal of glue residues, during the installation of pre-finished wood floors, laminate, LVT, SPC etc.

Stripcoll

Technical data at 20 °C – 60% r.h.

Appearance	Colourless liquid
Density	0,840 kg/litre
Storage	24 months in original sealed packaging
Packaging	1 litre bottles

How to use

Clean the still fresh adhesive with a cloth soaked in Stripcoll. In the case of water-based adhesives, first use a cloth or sponge moistened with water and then use Stripcoll to remove any remaining traces.

Change the rags often used to avoid spreading the glue on clean areas of the floor.

In the case of adhesive that has already hardened, this can only be removed mechanically, however Stripcoll can be useful for softening the adhesive residues and facilitating their removal. For this use, place a cloth soaked in Stripcoll on the adhesive to be removed and leave it to act for a few minutes.

Stripcoll does not affect the paints normally used for the creation of pre-finished parquet, in the case of oil-treated floors, check, before use, that the product does not damage the treatment.

After the treatment it is advisable to wash the floor with Pulito Parquet or Deteroil.

Use Stripcoll only on floors, do not use on furniture, fixtures and other surfaces.

Safety regulations

PRODUCT FOR PROFESSIONAL USE: Strictly comply with what is stated on the label and consult the safety data sheet before using the product.

Disposal

Dispose of the unused product and empty packaging in accordance with the local legislation in force.



The recommendations in this technical data sheet are given for information only and do not bind our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend checking the actual suitability for the intended use.

Rev 03 – 23/02/2022 – This technical data sheet cancels and replaces the previous one.