

# Greencleaner

Slow evaporation odourless aliphatic thinner

Slow evaporation aliphatic thinner specific for the dilution of oil-based impregnating agents or oil-urethane paints. Green Cleaner is a mixture of odourless cycloaliphatic hydrocarbons with excellent solvent power and good degreasing properties.

Available in 1 and 10 litre cans

## How to use

**To dilute.** Follow the instructions given in the technical data sheets of the individual products. Green Cleaner can be used as a substitute for common solvents based on white spirit or turpentine essence.

**To remove oils or waxes.** To remove residues of old oil or wax-based treatments from the wood or to remove oil that show drying difficulties, you can proceed as follows: Distribute Green Cleaner with a rag or roller on the surface to be treated, after 5 – 10 minutes remove the old treatment using a floor machine with a green disc. Remove all residues with a clean cloth. For the restoration it is recommended to proceed with an impregnation treatment (oil or wax).

## Notes

Do not use Green Cleaner in water-based products.

Always check compatibility with the product to be diluted.

Green Cleaner can be used to clean tools and machines used for the application of oils, waxes or oil-based paints.

## Safety regulations

Product for professional use. Strictly comply with what is stated on the labelling and consult the safety data sheet before using the product.

## Disposal

Dispose of the unused product and empty packaging in accordance with the provisions of the local legislation in force.



Varnishes &  
Finishing

## Greencleaner



The recommendations in this technical data sheet are given for information only and do not bind our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend checking the actual suitability for the intended use.

Rev 02 – 02/03/2021. This technical data sheet replaces the previous one.