Tovcol TP5 Vinyl glue for floating wood floors and laminate

Adhesive based on polyvinyl acetate in water dispersion for floating laying of tongue & groove wooden floors or laminate. It guarantees a fast setting and perfect transparency once dry. Tovcol TP5 is water resistant, classified as D3, according to EN 204 standard and is also suitable for general gluing of small wooden elements and DIY works, even exposed to water.



Tovcol TP5

Dati tecnici 20°C – 60% u.r.

Appearance	White paste
Density	1,10 kg/litre
Viscosity	9000 – 15000 mPas
Solid content	50%
Open time	10 minutes
Complete hardening	48 hours
Walkability	24 hours
Yield	100 – 150 ml/m²
Water resistance class: according to EN 204	D3
Application temperature	Da +10 a +35 °C
Storage	12 months in sealed packages at temp. > 10 $^{\circ}\text{C}$ – Frost sensitive
Tools cleaning	Immediately after use with water
Package available	500 ml bottles



Certifications

SOLVENT



How to use

The surfaces to be bonded must be clean and free from wood dust. Cut the spout according to the amount of adhesive you want to apply. Insert the spout into the joint of the floor board and press the bottle. Join the tapped part within 10 minutes and press to promote adhesion. Immediately clean any burrs with a damp cloth. The dry product can only be removed mechanically.

Safety rules

Product for professional use. Strictly comply with what is stated on the labelling and consult the safety data sheet before using the product.

Disposing of waste

Dispose of the unused product and empty packaging in accordance with the provisions of the local legislation in force.



Rev 05 – 02/03/2021. This technical data sheet replaces the previous one.





Tover S.r.l. Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY P. IVA 07783540011 - REA n. 920259 Tel. +39/011.7792823 - Fax.+39/011.7792749 www.tover.com - info@tover.com