

WPC Cover

Water-oil repellent protective treatment for WPC flooring

Water-based protective for the treatment of WPC elements, protects surfaces avoiding the absorption of oils and greases and the consequent formation of stains. It favours the maintenance of the original colour of the WPC products over time.

Technical data at 20 °C – 60% R.H.

Appearance	Opalescent liquid
Density	1,030 kg/litre
pH	7,5
Yield	15 – 20 m ² /litre
Dust dry	15 – 20 minutes
Overcoating	2 – 4 hours
Walkability	2 – 4 hours
Cleaning of tools	Immediately after use with water.
Storage	12 months in original sealed packaging at a temperature > +10 °C – Protect from freezing.
Packages available	1 liter bottles, 5 liter cans.

How to use

Thoroughly wash the surfaces to be treated with the WPC Cleaner detergent. As soon as the surface is dry, apply a coat of product, preferably by brush, taking care to leave a very thin and uniform thickness, avoiding accumulations in the grooves of the WPC elements. Normally a single coat of product is sufficient, if the result is not sufficiently uniform it is possible, after 2 – 4 hours, to apply a second coat of product without sanding, in the same way.

Given the large variety of WPC flooring on the market, we always recommend performing a preliminary test to check adhesion and any unwanted effects.

To restore a previously treated surface, wash with WPC Cleaner and, after drying, apply a coat of product as described above. For periodic cleaning use WPC Cleaner.

Notes

Shake the product before use.

Do not exceed the quantities applied, an excess of product is counterproductive, can cause detachment and lower protection.

Avoid product accumulation in the WPC grooves.

Protect from frost

Safety rules

Product for professional use. Strictly respect what is stated in the labelling and consult the safety data sheet before using the product.

Disposal

Dispose of unused product and empty packages in accordance with local legislation.



Varnishes & Finishing

WPC Cover



Certifications



The advice in this technical bulletin is given for information only and does not engage our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend verifying the actual suitability for the intended use.

Rev 04 – 30/05/2022.. This sheet cancels and replaces the previous one.

TOVER[®]



Tover S.r.l.

Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY
P. IVA 07783540011 - REA n. 920259
Tel. +39/011.7792823 - Fax. +39/011.7792749
www.tover.com - info@tover.com