

Rallenty

Retarder for water-based lacquers



Varnishes &
Finishing

Water-based additive suitable for all Tover water-based primers and lacquers to slow down their drying time, allowing to obtain a flawless application. Particularly useful when you have to work in a very hot environment or with very low ambient humidity due to heating or air conditioning systems.

Rallenty

Technical data at 20° C, 60 % R.H.

Appearance	Transparent liquid
Mixing ratio	Max 5% into the ready-to-use product
Storage	24 months in original sealed packages
Packaging	1 litre bottles

How to use

Add 5% of Rallenty into the primer or lacquer and proceed as usual. In the case of two-component products, first prepare the mixture and then add Rallenty.

Do not exceed the recommended quantities (5%): higher quantities could delay the complete hardening of the lacquer and decrease its mechanical properties. If a greater dilution than 5% of Rallenty is required, water can be used.



Notes

Exceeding the recommended usage percentage does not lead to any further improvement.

Rallenty is a product that helps finishing in non-optimal conditions, however it is always recommended, as far as possible, to avoid the application of water-based products during the hottest hours of summer days.

Safety standards

PRODUCT FOR PROFESSIONAL USE ONLY: Strictly comply with the labelling and consult the safety data sheet before using the product.

Disposal

Dispose of unused product and empty packaging in accordance with local legislation.

The advice in this technical data sheet is given as an indication and does not in any way engage our responsibility since the methods and conditions of use of the product are beyond our control. We recommend checking the effective suitability for the intended use. Rev 02 29 /04/2020 This technical data sheet replaces the previous one.