

Fullgap

Water-based acrylic sealant

Full Gap is a water-based sealant with polyacrylates, overcoatable, without silicones, characterized by high adhesion and water resistant. Thanks to its flexibility, it can be used to seal joints and cracks in wood floors (i.e. perimeter joints, skirting boards, etc.), wood in general and all porous materials used in the construction field. It can also be applied on damp but not wet surfaces. Perfectly suitable indoor to seal joints between building elements subject to medium stress. Once dry you can overcoat it. Available in white, maple, light oak, doussié/cherry, teak/light walnut, wengé, grey (RAL 7040) and sand oak. For indoor use only.

Technical data at 20 °C; 60% R.H.

Aspect	Thixotropic paste
Density	1,440 -1,460 kg/litre
pH	7,5 – 8,0
Open time	About 10 minutes
Hardening time	3 – 5 mm per day
Overcoating	24 hours minimum
Application temperature	> 10 °C – Frost sensitive
Storage	24 months in unopened original package at a temperature > 10 °C
Tool cleaning	With water, just after use
Available packaging	310 ml cartridge in a 12 unit box


Application

The surface to be treated has to be dry, compact, without dust, grease, wax or whatever may impede the perfect adhesion of the sealant.

To apply the product, put the cartridge into the gun, cut the top of the spout with a 45° inclination and apply it. During the application, keep the spout into the just extruded Full Gap in order to avoid air inclusion. Once applied, smooth the joint with a spatula or another suitable tool. In case of product contraction, repeat the operation. Possible deburrings can be eliminated by water.

After 24 hours Full Gap can be smoothed and overcoated. Before lacquering, check compatibility with the chosen finishing.

For more information about Full Gap yield read the table here below:



	A			
	3 mm	7 mm	10 mm	12 mm
3 mm	33 m	14 m	10 m	8 m
5 mm	20 m	8 m	6 m	5 m
7 mm	14 m	6 m	4 m	4 m
10 mm	10 m	4 m	3 m	2 m

Safety rules

For professional use only. Strictly respect the information reported on the label and consult the safety data sheet before using the product.

Waste disposal

Dispose the not used product and empty containers in accordance with local in force regulations.



Adhesives &
Sealants

Fullgap



Certifications



The information reported in present technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated.
Rev 09 – 11/04/2023. Current Technical Data Sheet replaces the previous one

TOVER[®]



Tover S.r.l.

Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY
P. IVA 07783540011 - REA n. 920259
Tel. +39/011.7792823 - Fax.+39/011.7792749
www.tover.com - info@tover.com