

Grey Free

Reviving product for greying wood



Cleaning &
Maintenance

Product for the treatment of greyed wood following ageing and deterioration caused by atmospheric agents. Grey Free allows you to remove the grey patina restoring the original colouring of the wood.

Grey Free can be used on any wooden item such as flooring, decking, shutters, cladding, etc. Also applicable vertically without sagging.

After rinsing and drying, the wood can be treated with any finishing product.

Grey Free

Technical data at 20 °C e 60% R.H.

Appearance	Transparent liquid
Density	1.00 kg/litre
pH	2
Drying	4 - 8 hours depending on environmental conditions and wood absorption
Yield	Approximately 5 m ² /litre
Application temperature	> +10°C
Storage	12 months in sealed packages
Tool cleaning	Water
Packaging	0.5 litre with sprayer, 1 litre bottles, 5 litre canisters



Instructions for use

The wood to be treated must be free from residues of previous varnishes or other treatments, coarse dirt and any wood fibres. Carry out a thorough mechanical cleaning of the wood with a hard brush, a buffing machine or pressure washer according to the type and extent of the surface to be treated. To remove traces of old oil treatments, it is possible to wash the floor with Re-Wood (see its technical data sheet).

Apply Grey Free by spraying it on the surface until saturated and leave it on for 10 – 15 minutes. Rinse thoroughly with water to remove dirt and product residues. Let it dry. If necessary, repeat the operation.

After the wood has completely dried, any type of protective impregnating/painting treatment for outdoors is possible.

Certifications



Notes

- It is advisable to always carry out a preliminary treatment test to verify the final aesthetic appearance.
- Grey Free is an acid product, avoid contact with metal elements or cementitious sub-floors; if it happens, take care to rinse thoroughly immediately.
- In the presence of wood with rotted areas, try to identify if it is possible to eliminate the cause that determined this phenomenon and act consequently.

Safety standards

PRODUCT FOR PROFESSIONAL USE. Strictly comply with the labelling and consult the safety data sheet before using the product. Wear gloves and protective clothing during application and ventilate the area well if applying indoors.

Disposal

Dispose of unused product and empty packaging in accordance with local legislation.

The advice in this technical data sheet is given as an indication and does not in any way engage our responsibility since the methods and conditions of use of the product are beyond our control. We recommend checking the effective suitability for the intended use.
Rev 04 – 03/06/2021. This technical data sheet replaces the previous ones.