

Resinal Wax

High resistance self-polishing wax

Resinal Wax is a metal bound wax ideal for the maintenance of floors in terracotta, linoleum, PVC, lacquered wooden floors and for the protection of stoneware and clinker. It is an emulsion of high-quality acrylic polymers which forms a water-repellent, washable, alcohol and foot traffic resistant protective film on the floor. It can be used both indoors and outdoors.

Technical data 20°C – 60% R.H.

Appearance	White liquid
Density	1.00 kg/litre
pH	9.5
Walkability	1 hour
Indicative yield	40 – 50 m ² /litre
Application temperature	From +5 to +35°C
Storage	24 months in original sealed packages – Frost sensitive
Packaging	1 litre bottles

Instructions for use

After laying the floor properly, uniformly distribute two or three thin coats of Resinal Wax using a previously moistened clean cloth, waiting 60 minutes between the coats. Any old layer can be removed using the Nettare due wax remover (consult data sheet of the product).

Notes

Always use only damp and well wrung out rags and cloths, avoiding excess of water. Shake before using. Do not exceed the amount of product applied.

Safety standards

PRODUCT FOR PROFESSIONAL USE. Strictly comply with the labeling and consult the safety data sheet before using the product.

Disposal

Dispose of unused product and empty packaging in accordance with local legislation.



Cleaning & Maintenance

Resinal Wax



Certifications

