

Xilolak

Water-based lacquer for outdoors

Water-based, waxy lacquer for outdoors with high water-repellency properties. For coating wooden elements and/or constructions like doors, windows, shutters, balconies, attics, fences, flower boxes, benches exposed outdoors and already treated with protective impregnating agents. It protects the wood from bad weather, it does not peel and leaves the surface smooth and soft to the touch. No yellowing. Thanks to efficient filter features it prevents decay and discolouration of wood caused by UV rays. It is recommended as a finishing treatment following the application of the Xilocolor water-based impregnating agent.

Technical data at 20 °C – 60% RH

Appearance	Milky liquid
Density	1.035 – 1.045 kg/litre
Touch dry	12 hours
Complete hardening	12 – 24 hours
Gloss	Glossy – 60 gloss Semi-glossy – 35 gloss Matt – 20 gloss
Application temperature	Min. +10 °C
Possible dilution	Water
VOC	55 g/litre cat A/e (WB), limit 130 g/litre (2004/42/CE)
Yield	10 – 12 m ² /litre
Storage	12 months in sealed packages at temperatures > +10 °C – Frost sensitive.
Tool cleaning	Immediately after use with water.
Packages available	1 – 2.5 – 10 litre jars

Application

Wood to be restored: sand the previous coat of lacquer that is not perfectly anchored to the surface using a 150/180 grit abrasive. Apply a thin layer of Xilolak by brush (without dilution) or by spray (with a dilution of 5 – 10%)

New wood: apply 1 or 2 coats of Xilocolor water-based impregnating agent as described in the relative technical data sheet. After 3-4 hours, apply a coat of Xilolak by brush (without dilution) or by spray (with a dilution of 5 – 10%).

Note

It is recommended not to use the product at temperatures below + 10 ° C.

Stir before use.

In case of brush application, brush along the direction of the vein.

Safety rules

PRODUCT FOR PROFESSIONAL USE. Strictly respect what is expressed in the labelling and consult the safety data sheet before using the product.

Disposal

Dispose of unused product and empty packages in accordance with the provisions of legislation local in force.



Varnishes &
Finishing

Xilolak



Certifications

The information contained in this technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated.

Rev 05 – 15/04/2021.
Current Technical Data Sheet replaces the previous one.

TOVER[®]



Tover S.r.l.

Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY
P. IVA 07783540011 - REA n. 920259
Tel. +39/011.7792823 - Fax. +39/011.7792749
www.tover.com - info@tover.com