

Bravo

One-part water-based sealer – Easy to use

Bravo is a one-part water-based sealer for on-site lacquering of wood floors. Suitable for the main wood species commonly used on the market, its special formulation allows for the first coat application while minimizing the risk of overlaps. The product is easy to sand and can be overcoated with all Tover water-based lacquers. It is also suitable for exotic woods commonly used in wood floors installation.



LACQUERS & FINISHES

Technical data at 20 °C, 60% R.H.

Aspect	Transparent liquid
Density	1.032 kg/l
pH	7,5 – 8,5
Dust dry	25 – 30 minutes
Touch dry	1 hour
Overcoating	Minimum 3 hours
Sanding	4 – 5 hours
Yield	10 – 12 m ² /litre
Application temperature	> 10 °C – Frost sensitive
Storage	12 months in original unopened packages at >10 °C
VOC	75 g/litre, cat A/i (WB), limit 140 g/litre (2004/42/CE)
Tool cleaning	Clean the roller immediately after use with water and neutral soap, using a “roller wringer” until the roller is no longer soaked in opalescent liquid. Rinse again with clean water. Store the rollers in appropriately diluted Soluzione S/28 cleaning solution; rinse with clean water before using them again.
Available packaging	5-litre canisters



CERTIFICATIONS



Application method

Sand the wood floor to obtain a smooth surface free from oils, grease, waxes or any old finishes.

Fill and level the surface using a water-based filler like Idrostucco RS/30 or a solvent-based one like Lega Stucco RS/A, mixing it with the wood dust. Complete the sanding cycle using 120 – 150 grit abrasive paper. Vacuum and carefully clean the wood surface before applying the sealer. Always ensure that the ambient conditions are suitable for lacquering. Shake the can well and apply one coat of Bravo using a roller or a brush. Once dry (after 4 – 5 hours), proceed with careful sanding using 180–220 grit mesh. Clean the surface thoroughly.

Alternatively, it is possible to apply the first coat of lacquer after approximately 3 hours and sand before applying the final topcoat.

Complete the lacquering cycle with one water-based lacquer, following the instructions in the relevant technical data sheets.

Notes

- In the case of thermo-treated wood or wood aged industrially with ammonia or other reagents, it is recommended to check the compatibility with the sealer to ensure there are no abnormal reactions or adhesion issues on such wood types. The same caution should be applied when working with oily or resinous woods, especially if they are uncommon species.
- Frost sensitive
- Do not pour the product directly onto the floor.
- Use a suitable container.
- Avoid lacquering the perimeter and the entire area in two stages. Treat small perimeter sections and immediately proceed with coating the adjacent area.
- During application, avoid direct sunlight on the floor.
- Avoid air drafts.
- Switch off the heating system, especially in case of underfloor heating.

Safety instructions

Product for professional use only. Strictly follow the instructions on the label and consult the safety data sheet before use.

Disposal

Dispose of unused product and empty containers in accordance with local regulations in force.



LACQUERS & FINISHES



CERTIFICATIONS



The information contained in this technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated.
Rev 01 – 19/11/2024. Current Technical Data Sheet replaces the previous one.