

Diluyente RMD/91

Slow evaporation aliphatic thinner

Diluyente RMD/91 is a slow evaporation aliphatic thinner specifically formulated for diluting solvent-based oil-wax impregnating products or oil-urethane hardwax oils. It is a mixture of nearly odourless dearomatized hydrocarbons with excellent solvent power and good degreasing properties. Does not darken the wood. Available in 10 - 5 - 1 liter drums.



**ADDITIVES &
THINNERS**

Application method

For dilution – For the recommended quantities, refer to the technical data sheets of the specific products to be diluted. In particular, for finishing products subject to directive 2004/42/CE, ensure that the maximum dilution limits specified for each product are not exceeded.

For removing oils or waxes – Apply Diluyente RMD/91 with a cloth or roller on the surface to be treated, remove the old treatment using a single-disc machine with a green pad. Wipe away all residues with a clean cloth.

For restoration, it is recommended to proceed with an oil or wax impregnation treatment.

Notes

- Do not use Diluyente RMD/91 with water-based or solvent-based products.
- Diluyente RMD/91 can be used as a substitute for common solvents such as mineral spirits or turpentine; however, always check compatibility with the product to be diluted.

Safety Regulations

Product for professional use only. Strictly follow the label instructions and consult the safety data sheet before use.

Disposal

Dispose of unused product and empty containers in accordance with local regulations.

The recommendations in this technical bulletin are indicative and do not imply any responsibility on our part, since the methods and conditions of product use are beyond our control. We recommend checking the actual suitability for the intended use.

Rev 02 – 23/04/2025. This sheet cancels and replaces the previous one.