

# Grip&Go

## Adhesion promoter for two-component water-based lacquers

Grip&Go is a two-component water-based sealer used as an adhesion promoter for lacquering existing wooden floors. It allows recoating of floors previously treated with traditional lacquers, UV lacquers, oils, and oil-based lacquers. Not suitable for wax-finished floors.

### Technical data at 20 °C, 60% R.H.

Appearance	Comp. A – White liquid Comp. B – Transparent liquid
Mix ratio	4:1 with B Plus hardener
Mixture density	1.040 kg/litre
pH	8.0
Pot-life	3 hours
Dust-free time	30 minutes
Touch dry	1 hour
Recoating time	Minimum 4 hours, maximum 16 hours
Possible dilution	Rallenty (max 5%) or water
Coverage	15 – 18 m <sup>2</sup> /litre
VOC	120 g/litre, cat A/j (WB), limit 140 g/litre (2004/42/EC)
Application temperature	+5 to +35 °C
Tool cleaning	Clean the roller immediately after use with water and neutral soap, using a roller wringer until it no longer releases milky liquid. If possible, rinse again with clean water. Store rollers in properly diluted Soluzione S/28 solution; rinse with clean water before reuse.
Storage	12 months in original sealed containers – Protect from frost
Packaging	Plastic cans of 2.0 + 0.5 litres and 4.0 + 1.0 litres

### Application instructions

Clean the floor thoroughly to remove dust and any other residues. Wet the surface with our wax-removing cleaner Clean&Go, allow it to act for 10 minutes, then rinse with clean water and allow to dry.

Perform an additional wash with MyFloor Cleaner to eliminate any remaining contaminants.

Mix the two components in the exact ratio (4:1) and apply one coat with a roller or brush. Then apply one coat of two-component water-based lacquer, respecting the recoating times (min 4 hours, max 16 hours). **Do not sand Grip&Go.**



LACQUERS & FINISHES



### CERTIFICATIONS



This process is usually sufficient to ensure good lacquer adhesion to the existing floor. For floors treated with oil/wax-based products or those maintained with wax-based products, sand with VF Pad or 220/320 mesh screen before washing with Clean&Go.

Pay special attention when dealing with heavily worn floors that have been maintained over the years with unknown products, which may not be suitable for wood. Generic floor cleaners may contain waxes or small quantities of silicones that accumulate and inhibit proper lacquer adhesion.

In case of doubt, it is always better to carry out light sanding before washing with Clean&Go. If possible, test on a small area before treating the entire floor.

For severely worn floors where the wood is no longer protected by existing lacquer/oil, this procedure cannot be used: sanding and full recoating of exposed areas is required.

## Notes

- Protect from frost
- Do not mix with other lacquers
- Avoid draughts
- Turn off heating, especially underfloor heating
- Although the A+B mixture remains fluid for several hours, application must be completed within the specified pot-life (3 hours) to obtain a continuous and uniform film

## Safety Regulations

For professional use only. Strictly follow label instructions and consult the safety data sheet before use.

## Disposal

Dispose of unused product and empty containers in accordance with current local regulations.



## LACQUERS & FINISHES



## CERTIFICATIONS



The recommendations in this technical bulletin are provided for informational purposes only and do not imply any responsibility on our part, as the methods and conditions of use are beyond our control. We recommend verifying the actual suitability for the intended use.  
Rev 01 – 19/04/2023. This sheet cancels and replaces the previous version.