

Prontostucco RS/40

Ready-to-use filler for parquet smoothing

Ready-to-use coloured water-based filler for smoothing and filling parquet. Easy to apply, odourless, and quick-drying. Available in Oak and Teak shades.

Technical data at 20 °C, 60% R.H.

Appearance	Coloured paste
Density	1.41 kg/litre
pH	8
Sandable	30 – 40 minutes
Possible dilution	Water
Indicative yield	About 8 m ² /kg
Application temperature	+10 to +35 °C
Tool cleaning	Immediately after use with water
Storage	12 months in original sealed packaging – Keep from freezing
Packaging	Buckets of 1 and 5 kg

Instructions for Use

Sand the parquet with coarse and medium paper to obtain a smooth surface free from oils, greases and waxes. Quickly and evenly spread the product over the floor with a stainless steel or non-metallic spatula, taking care to press as much product as possible into the cracks. For significant cracks, two applications may be necessary.

Notes

- Keep from freezing
- Use water for any dilution
- Can be overcoated with water and solvent-based products

Safety Regulations

Product for professional use. Strictly follow the labelling instructions and consult the safety data sheet before using the product. Wait for complete drying and then finish preparing the floor using a 100–120 grit abrasive. Before proceeding with the lacquering cycle, remove all excess filler.

Disposal

Dispose of unused product and empty containers in accordance with current local legislation.



CERTIFICATIONS



The recommendations in this technical bulletin are indicative and do not imply any responsibility on our part, since the methods and conditions of product use are beyond our control. We recommend checking the actual suitability for the intended use.

Rev 02 – 03/05/2024 This sheet cancels and replaces the previous one.