

Art Deco

Ready-to-use insulating product for wooden floors. It can be overcoated with water-based one- or two-component lacquers, oils and solvent-based lacquers. Available in neutral and coloured versions. Colours are fully miscible with each other and may also be lightened by mixing with the neutral version. Suitable for all wood species, ensuring the best results on light and absorbent woods. Easy to apply, it allows large surfaces to be stained evenly without overlapping marks.

Technical Data at 20 °C – 60% R.H.

Appearance	Transparent or coloured liquid
Density	0.9 – 1.0 kg/litre
Overcoating	Minimum 12 hours
Coverage	20 – 30 m ² /litre
Application temperature	From +10 to +35 °C
Tool cleaning	Solvente S 23
Storage	12 months in sealed original containers
Packaging	1 or 2.5 litres cans

Instructions for Use

Sand the floor to obtain a surface free from oils, grease, waxes, or previous coatings. Sand and fill the surface as usual. Complete sanding with grit 100–120.

Mix the product and apply with a wax spreader, cloth, or spatula, then spread evenly using a single-disc machine with a green or red pad.

Neutral version: used as a primer to regulate the absorption of water-based lacquers, especially for natural effect or lightly toned finishes. After at least 12 hours, without sanding, apply one coat of lacquer, sand with grit 180–220, then apply a second coat. For further details, refer to the technical sheet of the chosen finishing product.

Coloured version: allows for uniform staining even on large surfaces. Colorus can be mixed together or lightened with the neutral version. Touch-ups can be made within 24 hours of application using a cloth soaked in the coloured or neutral version, depending on requirements. For stronger lightening, Solver AD can be used. After at least 12 hours from touch-ups, proceed with the selected finish. Do not sand Art-Deco; if necessary, sand the first coat of lacquer.

Safety Instructions

Professional use only. Strictly follow the labelling instructions and consult the Safety Data Sheet before use.

Disposal

Dispose of unused product and empty containers in compliance with local regulations.



LACQUERS
& FINISHES



CERTIFICATIONS



The advice provided in this technical bulletin is given as a guideline only and does not imply any responsibility, as the methods and conditions of use of the product are beyond our control. We recommend verifying the actual suitability for the intended use.

Rev 01 – 01/10/2025.
This sheet cancels and replaces the previous version.