

BOOSTER MS

Additive for fast curing of Tover MS adhesives.

When added to Tover MS adhesives - Tovcol MS, Tovcol MS Start, Tovcol MS LVT the additive enables fast, deep and uniform curing of the adhesive, regardless of thickness. It is particularly useful when the adhesive itself is used as a filler for screed defects. It is also suitable when the adhesive is used as a joint filler between tiles. Once Booster MS has been mixed with the adhesive, it ensures an adequate working time, which can be extended by remixing at regular intervals.

Technical data at 20°C and 60% R.H.

Appearance	Brown paste
Mixing ratio	3.3% by weight of adhesive
Density	1.4 kg/l
Pot-Life	30 - 40 min
Open time	30 - 40 min
Setting time	6 - 8 hours
Foot traffic	6 - 8 hours
Sanding	Minimum 48 hours
Application temperature	10 - 35 °C
Available packaging	0,5 kg pot - pre-dosed for 15 kg adhesives 0,170 kg pot - pre-dosed for 5 kg adhesives
Storage	12 months in original sealed packaging at a temperature > 10°C

Subfloor preparation

Follow the instructions given in the technical data sheet of the adhesive into which Booster MS is mixed.

Application

Open the pot and mix its contents thoroughly. Pour the product into the bucket of the adhesive. Mix mechanically with a drill until a homogeneous mixture is obtained. Apply the entire bucket of adhesive and bond the flooring within the open time. The fields of application and the application method for the modified adhesive are those indicated in the technical data sheet of the glue itself.

Notes

- The open time may vary depending on the adhesive used.
- The open time may change depending on environmental conditions (hot and humid conditions shorten it, while cold and dry conditions extend it).
- Always use the entire quantity of Booster MS for one application. Incorrect mixing ratios may cause excessively fast curing or prevent the additive from working properly.
- If mixing with the adhesive is not carried out accurately, the adhesive mass may cure unevenly.

Safety instructions

Product for professional use. Strictly follow the information on the label and consult the Safety Data Sheet before using the product.

Disposal

Dispose of unused product and empty packaging in accordance with current legislation.



ADHESIVES &
SEALANTS

CERTIFICATIONS



The recommendations in this technical data sheet are provided for guidance only and do not in any way engage our responsibility, since the methods and conditions of use of the product are beyond our control. We recommend checking the actual suitability of the product for the intended use.

Rev 01 - 03/09/2026. This data sheet cancels and replaces the previous version.